
PART NO.	DESCR	IPTION		
11323	ADJUSTABLE FIRE RING, DOU	BLE FLANGE, PAINTED	1	
11323-1	ADJUSTABLE FIRE RING, DOUBLE FLANGE, UNPAINTED			
11323-2	ADJUSTABLE FIRE RING, DOU	BLE FLANGE, W/ S.A., PAINTED]	HINGED FOR ASH REMOVAL ——
11323-3	ADJUSTABLE FIRE RING, DOU	BLE FLANGE, W/ S.A., UNPAINTED		/
 Fire ring has an overall diameter of 33 1/8" x 11 1/4" high and is constructed of 3/16" thick steel (A1011). Fire ring is constructed with a formed (not welded) double flange for superior strength. Grate is constructed from 1/2" dia. A36 steel bars located on 1 1/8" centers. The four position theft proof grate adjusts from 13 3/4" to 19 1/4" above the firebed, and has a cooking area of 265 sq. inches. Grate handles are constructed of a 5/8" dia. A36 steel bar with stay cool spring grips suitable for public use. Ring is mounted using staples that allow the ring to tilt back for ease of cleaning or optional spade anchors. The spade anchors permanently anchor the fire ring to the ground. All joints are continuously welded. All exposed corners are chamfered for safety. Standard finish is a non-toxic black powder coat. Approximate weight = 107 lbs. 				
35 1/4" — Ø1/2" STAPLE —				
NOTE : 0		STAY C		SPADE ANCHOR (S.A.) OPTION APPROX. WEIGHT: 117 LBS
WARNING: MUST BE PERMANENTLY MOUNTED				
CUSTOMER APPROVAL : DATE :				
THIS DRAWING, WHICH CONTAINS PROPRIETARY INFORMATION, IS THE PROPERTY OF JAMESTOWN ADVANCED PRODUCTS CORPORATION. IT SHALL NOT BE REPRODUCED IN ANY MANNER NOR				



PHONE 800-452-0639 -- FAX 716-483-5398 -- WWW.JAMESTOWNADVANCED.COM

2855 GIRTS ROAD